

QL-30 QL-60

- One-Color Thermal Transfer Printer
- Print Labels 0.2" – 4.2" Wide



Compact Monochrome Label and Textile Printers

With middle-aligned media and high print speeds, the QL-30 and QL-60 thermal transfer label printers are the superior choice for consistent monochrome standalone or integrated labeling applications. Each system features a full-color touchscreen interface, complete with user help videos and standard Wi-Fi for wireless operation.

- Fast print speed up to 11.8 inches per second (59 ft. per minute)
- Print resolution up to 300 or 600 dpi
- Print width 0.2" to 4.2"
- ZPL emulation
- Built-in Wi-Fi

With the ability to print smaller labels at a 4mm minimum width, high accuracy and printing speeds of up to 11.8 inches per second, the QL-30 and QL-60 are both unmatched in the market. Integrating with most external applications, the QL-30 and QL-60 excel when paired with our Lusto-Lam laminating function. The QL-30 and QL-60 also provide ZPL emulation, allowing for seamless drop-in replacement of Zebra printers.

Their rugged, compact design makes both printers a great fit for anyone in need of an industrial printer with a small footprint guaranteed to provide years of service. The QL-30 and QL-60 are ideal for producing durable images for linear and 2D barcode printing, hazardous substance labeling, overprinting and surfaces exposed to extreme conditions for lengthy periods.

QL-30/QL-60 Specifications

Operation:

Ink Type:	Thermal transfer
Print Resolution:	QL-30: 300 dpi QL-60: 600 dpi
Print Speed:	QL-30: 1 ips (20 mm/sec) – 11.8 ips (300 mm/sec) QL-60: 1 ips (20 mm/sec) – 5.9 ips (150 mm/sec)
Print Area:	Width: 0.2" (4 mm) – 4.2" (106 mm) Length: 0.1" (3 mm) – 78.7" (2000 mm)
Media Sensors:	Gap, Reflective, Continuous
Connectivity:	High-Speed USB 2.0; Gigabit Ethernet; RS-232 (1,200 - 230,400 baud) (2) USB host device on rear panel (for keyboard, scanner, USB memory, bluetooth adapter) (1) USB host device on operation panel (for USB memory or service key) 802.11b/g/n WLAN , Digital I/O with 8 in- and outputs
Software:	Microsoft® Windows 10, 8, 7; Windows Server® 2012, 2008, 64/32-bit Drivers QuickLabel label creation and print management program suite Nicelabel® Enterprise or Desktop Software (optional)

Environmental & Physical:

Printer Operating:	32° F to 105° F (0° C to 40° C), 10% to 85% Relative Humidity (non-condensing)
Power Requirements:	100 - 240 VAC 50/60Hz, 1.5A/0.5A
Dimensions:	18.1" L x 9.9" W x 11.3" H (460 mm x 252 mm x 288 mm)
Weight:	22 lbs. (10 kg) without supplies
Optional Accessories:	Label Rewinder, Label Unwinder, Cutter, Cutter/Stacker, Present Sensor

Supplies:

Ribbon Supplies:	Each roll 1,476 ft. long (450 m)
Ink Type:	Thermal transfer
Labels and Tags:	
Width:	0.2" (4 mm) – 4.3" (110 mm)
Length:	0.1" (3 mm) – 78.7" (2,000 mm)
Thickness:	2.3 – 28.7 mil (0.06 mm - 0.73 mm)
Roll Size:	8.1" outside diameter (205 mm), 1.5" (38 mm) – 3.9" (100 mm) inside diameter
Types:	Gloss Paper, Matte Paper and Synthetic pressure-sensitive; Paper Tag Stock

Warranty:

Printer: 12 Month Manufacturer's Parts & Labor Warranty (excludes wear parts and supplies)



QuickLabel | Toll-free: 877-757-7978 | Tel: +1 401-828-4000
info@quicklabel.com | www.quicklabel.com